

TG-ALV-STTM

Tandem Full Height Turnstile

The TG-ALV-STTM is the most trusted, secure and reliable full height tandem turnstile available. It is installed in thousands of locations throughout the world and offers key product features and benefits only available from Online River. No other full height product comes close to the quality and performance of the TG-ALV-STTM.




Product Features

- Single or bi-directional access control
- Either rotation direction can be fail-safe or fail-secure
- Safe, controlled rotation that adjusts to pushing force of user
- Suitable for outdoor installations
- UL and CSE listed, CE marked

Product Benefits

- Integrates with existing access control system
- Provides single user passage control
- Helps reduce staffing requirements
- Highly reliable; provides long term continuous use
- Space saving design requires approximately 30" less side to side installation space than two individual turnstiles

FULL HEIGHT TURNSTILES



Available Models

TG-ALV-STTM-3 | Manual TG-ALV-STTM-6X | Electric

Common Applications

- Perimeter control and fence line security
- Time and attendance integration
- Employee and visitor access control
- Unmanned point of entry
- Single direction control and/or one-way exiting

Typical Installation Sites

- Corporate facilities
- Secured government facilities
- Distribution centers
- Manufacturing plants

Options

- Proximity and biometric reader integration
- Backup battery
- Credential status notification lights
- Turnstile open / closed status lights
- Enhanced environmental protection for severe environments
- Padded heel / arm guards

Safe and Reliable Operation

- Speed controlled rotation and automatic arm self-centering
- Mechanical anti-entrapment design
- Fail-secure operation provides free egress upon loss of power or fire system input
- Mode configuration through I/O or built in key locks
- UL listed

Electrical

Transformer 110 or 240VAC, 50 - 60Hz
 Peak Consumption 130W
 Operational Voltage VDC, 12/5

Access Control and Fire System Integration

The TG-ALV-STTM integrates easily to access control and fire systems through I/O (dry contact).

Operating Modes

Card in/card out; card in/free exit; free entry/free exit; exit only.

Available Finishes

- Hot dipped galvanized
- Powder coat | Powder coat over over galvanized
- #304 stainless steel | Powder coat over stainless steel

Dimensions

Dimensions shown in inches (mm).

